

Models	TCI-MF23	TCI-MF23	TCI-MF27	TCI-MF27	TCI-MF27
Capacity	2.000 kg	2.500kg	2.000kg	2.500kg	3.000kg
Center of gravity	600 mm	600 mm	600 mm	600 mm	600 mm
Lifting height	3.100 mm	3.100 mm	3.100 mm	3.100 mm	3.100 mm
A Height to top of canopy	2.000 mm	2.000 mm	2.100 mm	2.100 mm	2.100 mm
B Mast height collapsed	2.315 mm	2.315 mm	2.315 mm	2.315 mm	2.315 mm
C Frame opening	1.600 mm	1.600 mm	1.600 mm	1.600 mm	1.600 mm
D Width	2.400 mm	2.400 mm	2.500 mm	2.500 mm	2.500 mm
E Rear width	1.960 mm	1.960 mm	1.960 mm	1.960 mm	1.960 mm
G CDG on the rear of the truck	350 mm	350 mm	350 mm	350 mm	350 mm
H Overhand behing trailer	1.350mm	1.350mm	1.350mm	1.350mm	1.350mm
I Ground clearance	220 mm	220 mm	330 mm	330 mm	330 mm
J Mast tilt (front)	8°	8°	8°	8°	8°
K Mast tilt (back)	10°	10°	10°	10°	10°
L Face of forks to front tyres	900 mm	1.000 mm	950 mm	1.050 mm	1.050 mm
Forks carriage width	1.200 mm	1.200 mm	1.200 mm	1.200 mm	1.200 mm
Side shift of the mast	150 mm	150 mm	150 mm	150 mm	150 mm
Weight	2.300 kg	2.300 kg	2.400 kg	2.400 kg	3.250 kg
Speed	8 km/h	8 km/h	7 km/h	7 km/h	7 km/h
Kubota engine	V1305– 33 cv	V1505– 36 cv	V1505– 36 cv	V1505– 36 cv	V1505 T– 45cv
Pneumatics	23x8,5-12	23x8,5-12	27x10-12	27x10-12	27x10-12
Diameter	574 mm	574 mm	710 mm	710 mm	710 mm
Width	223 mm	223 mm	266mm	266mm	266mm
					Extensor